



ARMSTRONG RETAIL 12 mm

- Armstrong RETAIL offers a smooth, unperforated contemporary visual that provides energy savings due to its high level of light reflectance
- Excellent light reflectance (87%)
- Ideal for retail environments



ARMSTRONG RETAIL 12 mm

Edge details		Board 														
Thickness (mm)		12														
Dimensions (mm)		600 x 600 1200 x 600														
System		Exposed demountable - System C Exposed - Bandraster, demountable - System I.3 Exposed - Corridor, demountable - System F.3														
Weight		3.1 kg / m²														
Colour		White														
Sound absorption		EN ISO 354 α _w = 0.15(L) as per EN ISO 11654 - Class E <table><tr><th>Frequency f (Hz)</th><td>125</td><td>250</td><td>500</td><td>1000</td><td>2000</td><td>4000</td></tr><tr><th>α_p</th><td>0.30</td><td>0.25</td><td>0.15</td><td>0.10</td><td>0.10</td><td>0.20</td></tr></table> NRC = 0.15 as per ASTM C 423	Frequency f (Hz)	125	250	500	1000	2000	4000	α _p	0.30	0.25	0.15	0.10	0.10	0.20
Frequency f (Hz)	125	250	500	1000	2000	4000										
α _p	0.30	0.25	0.15	0.10	0.10	0.20										
Sound attenuation		EN ISO 10848-2 D _{n,f,w} = 31 dB as per EN ISO 717-1														
Fire reaction		Euroclass A2-s1, d0 as per EN 13501-1 RUS KM1 (G1, V1, D1, T1) as per FZ 123														
Light reflectance		87%														
Thermal conductivity		λ = 0.060 W/m K as per EN 12667														
Humidity resistance		70% RH														
Indoor air quality		<div> A+</div> <div> E1</div>														
Cleanability	 															
Sustainability	<div> EN ISO 14021 46%</div> <div> BIOBLENDED WOOL EC 1272/2008 Annex G</div> <div> BLAUER ENGK ZULassung</div>															

Products may vary from country to country. Please contact your local sales representative.
For further information and legal notice, please visit our website.